KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

RC-5B4

Wall Plate Insert − 4−Button Auxiliary Control Panel

The RC−5B4 is a 4−button auxiliary control panel with backlit RGB buttons. It can be used as an auxiliary controller when connected via K−NET™ to a master room controller (such as the RC−74DL).

FEATURES

- 4 Button Faceplate - With backlit, configurable color buttons.
- K-NET™ Control Channel - For connecting individual and daisy−chaining multiple panels.
- K-Config Installation and Configuration.
- USB Port - For upgrading the firmware and setting the K−Net ID number.
- Dimensions - 5cm x 2.4cm x 4.7cm (1.97" x 0.94" 1.85") W, D, H.
- Size - Dual insert, can be used in any compatible opening: wall boxes, TBUS, etc. Supplied with black and white front plates.

RC-5B4

TECHNICAL SPECIFICATIONS

PORTS:	2 K−NET on terminal block connectors, 1 USB for programming.
CONTROLS:	4 buttons.
POWER CONSUMPTION:	5V DC, 40mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	−40° to +70°C (−40° to 158°F).
HUMIDITY:	10% to 90%, RHL non−condensing.
DIMENSIONS:	5cm x 2.4cm x 4.7cm (1.97" x 0.94" 1.85") W, D, H.
WEIGHT:	0.14kg (0.31lbs) approx.

CONFIGURATIONS